## PATENT ABSTRACTS OF JAPAN

(11)Publication number:

07-060955

(43) Date of publication of application: 07.03.1995

(51)Int.Cl.

B41J 2/01

B41J 2/175

(21)Application number : **05-214031** 

(71)Applicant: CANON INC

(22) Date of filing:

30.08.1993

(72)Inventor: ASAI AKIRA

## (54) INK JET RECORDING HEAD AND INK JET RECORDER EQUIPPED WITH THE RECORDING HEAD

$$i(r) = \frac{1}{\theta r d(r)}$$

(57) Abstract:

i

Π

 $q(r) = i(r)^2 \rho d(r)$ 

novel heating element wherein heating distribution on a surface of a resistor is equalized and its recorder by a method wherein a heating

PURPOSE: To obtain a recording head having a

resistor has a heating part of an approximately circularly annular or fan-like annular surface shape, and its thickness is varied inversely proportional to a distance in a radial direction from a central point of the surface shape.

from a central point of the surface shape. CONSTITUTION: When voltage is impressed by making a current (I) flow radially along a radial direction of a heating resistor, a thickness d (r) of

direction of a heating resistor, a thickness d (r) of a heating part of the heating resistor is varied inversely proportional to a radial distance (r) from a center of a surface shape. Thereby, a current density i (r) at any point on the heating part at a radial distance (r) apart from the center

comes to be as given by the formula (I). In the formula  $\theta$  is an angle of a fan-like annulus ( $2\pi$  in between 'the resistivity ( $\rho$ ) of the resistor and a

 $q(\mathbf{r}) = \frac{I^2 \rho}{\theta^2 r^2 d(\mathbf{r})}$ 

the case of a circular annulus). Relation between 'the resistivity ( $\rho$ ) of the resistor and a heating value q (r) per unit time unit area is as given by the formula II. Therefore, the formula III is obtained.

## **LEGAL STATUS**

[Date of request for examination] 30.06.1999 [Patent number] 3157964 [Date of registration] 09.02.2001